

PROVANTAGE KRAFTLINER

Technical Data Sheet



Benefits

- Made of predominantly fresh fibre
- Excellent strength parameters
- Stable and uniform moisture and glue absorption properties
- Reliable runnability and processing properties



End-uses

- Pharma & Medical
- Clothing & Textiles
- Beverages
- Dairy & Deep-frozen
- Fresh Fruit & Vegetables
- Meat, Poultry & Seafood
- Mobility
- Industrial & Chemicals



Typical values

Properties	Method	Unit of measure	Substance (g/m²)												
			100	110*	125*	135*	150	160	170*	186*	200	225	250	275	300
Moisture	ISO 287	%	7.8												
Bursting strength	ISO 2758	kPa	460	530	580	610	680	700	730	810	850	914	966	1050	1176
SCT _{CD}	ISO 9895	kN/m	2.00	2.30	2.50	2.70	3.00	3.20	3.40	3.70	4.00	4.40	5.00	5.40	6.00
Tensile stiffness index _{MD}		kNm/g	12						11						
Tensile stiffness index _{CD}			5												
Cobb ₆₀ (top)	ISO 535	g/m²	30												
Cobb ₆₀ (bottom)			70												
Dennison test	TAPPI 459 om-08	No.	18												
Gurley	ISO 5636-5	s	max. 150												



Certificates:

Food contact
ISO 9001
ISO 14001
ISO 45001
FSC®
PEFC

Mondi Świecie
Issued: 01/02/2026
latest version available on
mymondi.mondigroup.com

Test conditions:

Typical values after conditioning,
measured at 50 ± 2% RH and 23 ±
1°C (ISO 187 : 1990)

*ECO Premium Service, fast delivery option