

JAC GRAPHICS

JAC OPAQUE FSC

Print carrier

JAC® OPAQUE is a range of opaque self-adhesive papers for re-labelling applications where the existing texts must be completely concealed, e.g. for text or price corrections. These self-adhesive papers display excellent opacity.

JAC® SCRIPT OPAQUE FSC A calendared, white writing paper displaying very good printing properties. The face material is made from FSC® certified paper (FSC MIX CREDIT CU-COC-807907).

JAC® CHROMO GLOSS OPAQUE FSC A specially coated, white, gloss paper which is particularly suitable for multi-colour labels. The face material is made from FSC® certified paper (FSC MIX CREDIT CU-COC-807907).

JAC® CHROMO MATT OPAQUE FSC A specially coated, white, matt paper which is particularly suitable for the multi-colour offset printing of high-quality labels. The face material is made from FSC® certified paper (FSC MIX CREDIT CU-COC-807907).

Average values

	SCRIPT OPAQUE FSC	CHROMO GLOSS OPAQUE FSC	CHROMO MATT OPAQUE FSC
Weight (g/m ²)	86	102	103
Thickness (µm)	85	100	100
Opacity (%)	98		
Shelf life of laminate ¹⁾ (years)	2	2	2

¹⁾ Refers to adhesion and printability when stored in original packaging in dark, dry conditions at a temperature of 22 ± 2°C and a relative humidity of 50% ± 5%

For information regarding EHS regulation please visit our website under downloads "Guidelines for Use "5.12 Product Compliance JAC® Offset"

For technical guidance please visit our web side under downloads "Guidelines for use "– Offset printing"

Adhesive

DURO D 2000 is a dispersion-based permanent acrylic adhesive displaying very good processing properties and excellent guillotining behaviour. Its good adhesion permits use on a diversity of surfaces, such as paper, steel, glass etc. It also displays very good UV stability.

Average values

	D2000
Adhesion (N/25 mm) (FTM 2 on st. steel/20 min. bond time)	9.2
Tack (N/25 mm) (FTM 9 on glass)	9.6
Recommended minimum application temperature (°C)	> +5
Heat resistance up to 24 hrs (°C) up to 1 hr (°C)	+80 +110
Resistance to cold (°C) ¹⁾ down to	- 40

¹⁾ Not fully resistant until after adhesion reaches full strength – after at least 24 hrs

Silicone paper

B 85 – a siliconized, wood-free, special-purpose paper. It is moisture-stabilized through a special coating on one side. B85 displays high dimensional stability and excellent flatness.
(available ex stock with Chromo Gloss Opaque FSC).

B 110 – a siliconized, wood-free, special-purpose paper. It is moisture-stabilized and displays very high dimensional stability and excellent flatness.
(All grades available ex stock)

Average values

	B 85	B 110
Weight (g/m ²)	78	86
Thickness (µm)	82	87

Guarantee and liability

Issue December 2016

All Avery Dennison and JAC® statements, technical information and recommendations are based on tests believed to be reliable but do not constitute a guarantee or warranty. All Avery Dennison and JAC® products are sold with the understanding that purchaser has independently determined the suitability of such products for its purposes.

All Avery Dennison and JAC® products are sold subject to Avery Dennison's general terms and conditions of sale, see <http://terms.europe.averydennison.com>



www.jacgraphics.com