

No. AJHL1610011324FB

Date: OCT.24, 2016

Page 1 of 6

The following sample(s) was / were submitted and identified on behalf of the client as:

Sample Description: COATED POLYESTER FABRIC

Color: WHITE

<u>Thickness</u>: 150µM <u>Density</u>: 140GSM

Composition: 55% POLYESTER, 45% COATING

Supplier:

Manufacturer:

<u>Country of Destination</u>: EUROPE <u>End Use Application</u>: INKJET MEDIA

# **Test Requested:**

To determine the flammability (building materials class B1) in accordance with DIN 4102-1 (May 1998) Fire behaviour of building materials and elements Part 1: Classification of building materials, Requirements and testing

Test Results: -- See attached sheet --

Classification: The tested sample meets class B1 building materials requirements of DIN 4102-1 (May

1998).

### **Test Period:**

Sample Receiving Date

: OCT.08, 2016

Test Performing Date

: OCT.08, 2016 TO OCT.24, 2016

Signed for and on behalf of SGS-CSTC Co., Ltd. Anji Branch



**Technical Manager** 



Unless otherwise agreed in writing, this document is lasued by the Company subject to its General Conditions of Service printed overlast, available or request or secessible at http://www.sgs.com/en/Terms-and-Conditions/Service-forms and Conditions for Electronic Documents, subject to Terms and Conditions for Electronic Documents, and the Company and Conditions for Electronic Documents again. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein, Any holder of this document is advised that information contained hereon reflects the Company's Indidings at the time of its intervention only and within the limits of Cleant's instructions, if any. The Company's sole responsibility is to its Client and this document does not expense to a transaction from exercising all their rights and obligations under the transaction document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized afterstation, forgery or falsification of the content or septement of this document is unlawful and offsenders may be prosecuted to the fullest stant of the law. Unless otherwise stated the Attention Company and its content of sealing and company and content or results shown in this test eport refer only to the sample(s) tested and such sample(s) are retained for 30 days only.



No. AJHL1610011324FB

Date: OCT.24, 2016

Page 2 of 6

### I. Test conducted

This test was conducted as per DIN 4102-15:1990 DIN 4102-16:1998 and DIN 4102-1:1998 Clause 6.2, and Classification in according to DIN 4102-1 (May 1998) Clause 6.1-Class B1 materials.

# II. Sample details

General description / Color	COATED POLYESTER FABRIC / White
Density	About 144 g/m <sup>2</sup>
Size of sample	1000mm×190mm & 190mm×90mm

### Conditioning

Prior to testing, the sample was conditioned at least 14 days to constant mass at a temperature of  $23 \pm 2$  °C, and a relative humidity of  $50 \pm 6$  %.

### III. Test results

# 1) "Brandschacht" Test according to DIN 4102-15 &16

Exposed surface: The front face

	Results of "Brandscha	acht" Test	t (part 1)			
Line		Unit	Test assemblies No.			
No.		OTHE	Lengthwise	Widthwise		
1	Specimen fixings according to DIN 4102 part 15, table	1	=			
2	Max. flame height above lower sample edge;	cm	50	50		
3	Time 1)	min:s	0:15	0:18		
	Melting/burning through					
4	Time 1)	min:s	0:03	0:04		
	Back of specimen					
5 .	Flaming/glowing, Time 1)	min:s	0:02	0:03		
6	Discolouring, Time 1)	min:s	0:04	0:05		
	Burning droplets					
7	Begin 1)	min:s	0:06	0:08		
	Amount					
8	Specimen material falling off in separate droplets		1	7		
9	Specimen material falling off continuously		√	√		

To be continued...



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overlead, swaleble on request or accessable at http://www.sgs.com/en/Terms-and-Conditions.agps.and, for electrocic format documents subject to Terms and Conditions for Electrocic Documents at http://www.sgs.com/en/Terms-and-Conditions/Ter

No.301, Suright Road, 2 Block, Suright Industry Zone, Anj County, Zhejiang Province, China 313300 t (26-572) 501862 f (26-572) 501862 www.sgs.group.com. 中国 - 浙江 - 安吉县阳关工业园二区阳光大道301号 邮稿: 313300 t (26-572) 501862 f (26-572) 501862 e sgs.china@sgs.co



No. AJHL1610011324FB

Date: OCT.24, 2016

Page 3 of 6

	Results of "Brandscha	cht" Test	(part 2)	, 100 m a 100 m		
Line		Unit	Test assemblies No.			
No.		Ont	Lengthwise	Widthwise		
	Burning parts					
10	Begin 1)	min:s	0:12	0:15		
11	Parts of sample falling off separately		√	✓		
12	Parts of sample falling off continuously		1	1		
13	Duration of continued combustion on mesh base (max.)	min:s	No	No		
	Burner flame impairment by dripping/falling material		No	No		
14	Time 1)	min:s	1	1		
	Premature ending of test		1	1		
15	End of burning at specimen 1)	min:s	1	1		
16	Time when test terminated (if applicable) 1)	min:s	I	1		
	Burning after end of test		No	No		
17	Duration	min:s	7	1		
18	Number of specimens		7	/		
19	Front of specimen		- 1	/		
20	Back of specimen		1	/		
21	Height of flame	cm	1	1		
	Glowing after end of test		No	No		
22	Duration	min:s	1	1		
23	Number of specimens		1	1		
24	Front of specimen		1	/		
25	Back of specimen		/	1		
26	Top half of specimen		1	/		
27	Bottom half of specimen		1	/		

To be continued...



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overlead, available on request or accessible at http://www.egs.com/ser/Terms-and-Conditions.gov.and-for-described forms-and-Conditions for Electronic Documents at http://www.egs.com/ser/Terms-and-Conditions-Terms-and-

No. 301, Sunight Road, 2 Bood, Sunlight Industry Zone, Anj County, Zhejang Province, China 313300 ( 多572 503825 f 後572 503829 www.s.gsgroup.com.cn 中国 ·浙江 · 安吉县阳光工业园二区阳光大道301号 邮编:313300 ( 多572 503825 f 後572 503829 \* sgs.china@sgs.com



No. AJHL1610011324FB

Date: OCT.24, 2016

Page 4 of 6

	Results of "I	Brandschacht" Test	(part 3)				
Line		Unit -	Test assemblies No.				
No.		Offit	Lengthwise		Widthwise		
	Residual length					III III III III III III III III III II	
28	Single results	cm	54	57	55	57	
20	Single results	Cili	52	53	56	57	
29	Average of the single results	cm	54.0		56.3		
	Smoke temperature						
30	Max. of average	$^{\circ}$	146.2		145.4		
31	Time 1)	min:s	06:55		07:12		

Note: 1) time from start of testing

#### Class B1 materials:

If the residual length measured after the first test is 45cm or greater, further tests are not required.

# 2) Normal Flammability Test according to DIN 4102-1 Clause 6.2

Flame application: [ √ ] bottom edge ignition, [

] surface ignition

Davamatar	Lengthwise				Crosswise					
Parameter	1	2	3	4	5	6	7	8	9	10
Reaching the measuring mark within 20 seconds(Yes/No)	No	No	No	No	No	No	No	No	No	No
Self extinguishing of the flame (s)	15	15	15	15	15	15	15	15	15	15
Max. flame height (cm)	5	6	6	5	5	4	5	5	4	5
End of afterflaming (s)	15	15	15	15	15	15	15	15	15	15
End of afterglowing (s)	15	15	15	15	15	15	15	15	15	15
Molten dripping(Yes/No)	No	No	No	No	No	No	No	No	No	No
Smoke developments (visual impression)	Slight					Slight				

All timings are from start of testing.

To be continued...



No. 301, Sunlight Road, 2 Blook, Sunlight Industry Zone, Anji County, Zhejlang Province, China 313300 🔞 (96-572) 50(9625 🖁 (96-572) 50(9625 www.sgsgroup.com.cn 邮编:313300 t (95-572) 5019625 f (95-572) 5019629 \* sgs.china@egs.com

<sup>\*</sup>Reduction in number of test (DIN 4102 Part 16, clause 5.2)



No. AJHL1610011324FB

Date: OCT.24, 2016

Page 5 of 6

#### IV. DIN 4102-1:1998 Criteria for classification

- All materials, except flooring, may be classed as B1 materials if they meet the following requirements a) and
  b):
- a) The test using the 'Brandschacht' apparatus described in DIN 4102-15 (cf. subclause 6.1.3.1) shall be deemed passed if
- The mean value for the residual length (portion of specimen that has not burned or charred; cf. subclause
- 9.1 of DIN 4102-16) of each specimen is at least 15 cm and no individual values are lower than 0 cm,
- The mean effluent temperature does not exceed 200 °C in any test,
- The requirement for the residual length of each specimen is met even where there is afterflame, afterglow, or smouldering.
- b) Pass DIN 4102-1: 1998 sub-clause 6.2.3 Ignitability Test if
  For each specimen, flaming doesn't reach the gage mark within 20s after flame application.
- 2) Materials may be classed as **B2** materials if they pass the ignitibility test specified in DIN 4102-1: 1998 subclause 6.2.5.

For each specimen, flaming doesn't reach the gage mark (150mm marks) within 20s after flame application.

3) Combustible materials which cannot be classed as B1 or B2 materials shall be classed as B3 materials.

#### STATEMENTS:

This test report does not replace any mandatory certification of the product that may be required.

The test results relate to the behaviour of the test specimens of a product under the particular conditions of the test; they are not intended to be the sole criterion for assessing the potential fire and smoke hazard of the product in use.

To be continued...



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overfeat, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions app; and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at Into//www.sgs.com/en/Terms-and-Conditions/Te




No. AJHL1610011324FB

Date: OCT.24, 2016

Page 6 of 6

**Photo Appendix:** 



SGS authenticate the photo on original report only

\*\*\* End of Report \*\*\*



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printer overlead, available or request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspy and, for electronic format documents subject to Terms and Conditions for Electronic Documents are subject to Terms and Conditions for Electronic Documents are subject to Terms and Conditions for Electronic Documents are subject to Terms and Conditions are subject to Terms and Conditions of Terms-and-Conditions for Terms-and-Conditions of Terms-and-Conditio