

Warszawa 11.03.2024

## TDS FILE myMEDIA 4412 Mesh Flag FR

### PRODUCT DESCRIPTION:

- 100% polyester warp knitted fabric with a semi glossy finishing
- Good soft texture and double ink penetration effect

### PRINTING METHOD:

DIRECT and TRANSFER SUBLIMATION

APLIKATIONS: Flags, banners

PROPERTIES	TEST METHOD	METRIC / IMPERIAL
Total weight	DIN EN ISO 2286-2, ASTM D751	115g/sqm 3.3 oz/sq.yd
Base fabric	DIN 60001, ASTM D7641	100% polyester
Weave method	N/A	Warp-knitted 3 bar
Shrinkage	N/A	≤2% (210°C, 30s)
Flame resistance	DIN 4102-1-B1, NFPA 701 Test1	DIN 4102-1-B1, NFPA 701 Test1
Recommend Fixation Temperature	N/A	190- 210°C, 1-2 min
Yellowing Temperature	SUPRKC REX-C400, 30s	≥ 210°C
Width Available	DIN EN ISO 3759, ASTM D751	Max 320cm, 126"
Standard Length	DIN EN ISO 3759, ASTM D751	100m, 110yds

**NOTE:** It is normal that the weight of most products will have an average fluctuation of 5%. All above information shall only use as a guide; buyers shall independently test and determine the products suitability. The mentioned data are average of test result and should not be used for the purpose of lawsuit of warranty