



## YUPO EUROPE GmbH

Willstätterstr. 30  
D-40549 Düsseldorf  
Tel. +49-211 520 54 360  
Fax +49-211 520 54 368  
[www.superyupo.com](http://www.superyupo.com)

January 2015

## Recommended Lamination-Films for YUPOTako

YupoTako's possible applications are endless. One of them is the usage as a floor graphic. To reach the safety requirement for this application, it is necessary to apply an anti-slip lamination film after printing. Here are some tested lamination films which can be used on YUPOTako's surface. Although we tested the material with our products, we recommend testing before going into production.

Producer	Product	Application	Type	Description	Adhesive	Contact
Mactac	PF 6300	Floor lamination for interiors	Cold lamination	PVC film 125 µm	Acrylic adhesive	<a href="http://www.mactac.de">www.mactac.de</a>
Mactac	PF 6301	Floor lamination for interiors	Cold lamination	PVC film 100 µm	Acrylic adhesive	<a href="http://www.mactac.de">www.mactac.de</a>
Seal Graphics	UV Sol Lam	Image protection for indoor and outdoor	Cold lamination	PVC film, 70 µm	Acrylic adhesive solvent base	<a href="http://www.sealgraphics.com">www.sealgraphics.com</a> <a href="http://www.weltenet.de">www.weltenet.de</a>
AVD	Ecotec 300 matt/sand	Floor lamination for outdoor	Cold lamination	PVC film, 100 µm	Polyacrylic	<a href="http://www.avd-online.de">www.avd-online.de</a>
AVD	Ecotec-Folien	Protection film for indoor and outdoor	Cold lamination	PVC film in several thicknesses	Polyacrylic	<a href="http://www.avd-online.de">www.avd-online.de</a>
GMP	Pronex-Floor-Folien	Protection film for floor lamination	Cold lamination	PVC film 200µm	Polyacrylic	<a href="http://www.gmp-germany.de">www.gmp-germany.de</a>
ATP	GL - 412	Floor advertisement, POP-UP-Displays	Cold lamination	Soft PVC Film, 100 µm	Polyacrylic, permanent	<a href="http://www.atp-ag.com">www.atp-ag.com</a>
ATP	GL - 420	Floor advertisement, POP-UP-Displays	Cold lamination	Soft PVC Film, 170 µm	Polyacrylic, permanent, pH-neutral	<a href="http://www.atp-ag.com">www.atp-ag.com</a>
Drytac	Interlam EcoTex	banner stand graphics, signage display in high traffic areas, counter mats, placemats	Cold lamination	Pebble Textured Polypropylene 140µm	Aqueous Acrylic (Pressure Sensitive)	<a href="http://www.drytac.com">www.drytac.com</a>

\*These figures are the result of in-house tests. Actual results may vary.



**YUPO®**

**YUPO EUROPE GmbH**

Willstätterstr. 30

D-40549 Düsseldorf

Tel. +49-211 520 54 360

Fax +49-211 520 54 368

[www.superyupo.com](http://www.superyupo.com)

---

January 2015

### **Additional Lamination Recommendation:**

1. Printed image must be completely dried or cured before lamination process.
2. As YUPOTako is a very compressive product, it is essential to reduce the pressure as much as possible. Especially on big size applications (more than 3m), there could appear some wrinkles if the pressure is too high.

### **Application:**

1. Clean the part of the floor where Tako has to be applied very carefully to ensure the best possible adhesion power.
2. For re-using the banner, apply the liner on the adhesion side before storing.
3. Do not roll the material by hand. If you have to roll it up, please use a core with a diameter of 7,6cm.

For any additional information or recommendation, please feel free to consult with our Technical Department.