

Foil Silver/Gold Gloss

FACESTOCK

Foil Silver/Gold Gloss

Finish Gloss

Description Aluminium foil laminated on satin 50 gsm paper. Available in gloss and matt finish. Color Silver, Gold

Applications Decorative labels. High quality labels for cosmetics, spirits and the food industry in Suitable for printing on conventional offset, offset UV, letterpress (conventional and UV), UV Printing techniques Suitable for printing on conventional onset, onset of a state of the state o

Property	Norm	Units	Value	Tolerance
Substance	ISO 536	g/m²	72	67,7 - 76,3
Thickness	ISO 534	μm	65	58,5 - 71,5

ADHESIVE

A251

Description General use acrylic permanent adhesive including smooth and slightly rough or curved surfaces. Shelf life From the date of manufacture 2 years in 20°C and RH 50%

Method	Units	Value	Tolerance
FTM 1	N/25mm	15,4	≥ 12,3
FTM 8	min	100	≥ 60
FTM 9	Ν	10,3	≥ 7,8
	٥C	5	
	٥C	-20	
	٥C	80	
	FTM 1 FTM 8	FTM 1 N/25mm FTM 8 min FTM 9 N °C °C	FTM 1 N/25mm 15,4 FTM 8 min 100 FTM 9 N 10,3 °C 5 °C -20

LINER **WK80**

One-side coated white liner with good lay-flat characteristics. Suitable for sheeting. Description Available only in solid back

Color White

Property	Method	Units	Value	Tolerance
Substance	ISO 536	g/m2	80	± 4%
Thickness	ISO 534	μm	81	± 4

CERTIFICATES

Product approvals and usage certificates Contact with foodstuff (BfR XXXVI) - Facestock and Liners (paper) Packaging and packaging waste Directive 94/62/CE Electric and electronic equipment (RoHS) Directive 2011/65/EU EN 71-3 Toy safety EN 71-9Toy safety Direct contact with foodstuffs (ISEGA) - Adhesives

Values are subject to change without notice. Last updated 30/04/2020

• The technical information that appears in this document reflects our knowledge and experience, but should only be considered as a general guideline.

Our self-adhesive mill holds ISO 9001 quality certification, ISO 14001 and EMAS environmental certifications and ISO 50001 energy management system certification. Gripper products are available with PEFC™ and FSC® chain of custody certificates upon request.

