

Warszawa 17.01.2024

TDS FILE**MY4332 myMEDIA4332 SmartStretchTex FR 200g****PRODUCT DESCRIPTION:**

- 100% polyester warp knitted fabric with soft hand feel
- Offers good opacity and anti-wrinkle ability
- Suitable stretch,

APPLICATION:

widely be used as stretch display, tradeshow, POP UP.

PRINTING METHOD:

DYE SUB DIRECT / DYE SUB TRANSFER PAPER / LATEX

| PROPERTIES | TEST METHOD | METRIC / IMPERIAL |
|--------------------------------|---|-------------------------------|
| Total weight | DIN EN ISO 2286-2, ASTM D751 | 200g/sqm 5.9 oz/sq.yd |
| Base fabric | DIN 60001, ASTM D7641 | 100% polyester |
| Weave method | N/A | Warp knitted |
| Shrinkage | 210°C, 30s | ≤2% |
| Shielding rate | ANSI PH2.19, ISO 5/2 | (64+/-5)% |
| Elasticity | Length*Width=200*50mm Speed=100mm/min, Tension=20N | Warp: (7+/-2)% Weft (17+/-3)% |
| Flame Resistance | DIN 4102-1-B1, NFPA701 Test1, | DIN 4102-1-B1, NFPA701 Test1, |
| Recommend fixation temperature | N/A | 190°C, 30s |
| Width Available | DIN EN ISO 3759, ASTM D751-2006 | Max 320cm, 126" |
| Standard Length | DIN EN ISO 3759, ASTM D751-2006 | 50m, 55yds |

NOTE: It is normal that the weight of most products will have an average fluctuation of 5%. All above information shall only used as a guide; buyers shall independently test and determine the products suitability. The mentioned data are average of test result and should not be used for the purpose of lawsuit of warranty