

PANORAMA INNOVA

panoRama Innova 20UV / 30UV / 40UV / 50UV is a perforated pressure sensitive window film designed for short to mid-term applications so as events. This product offers 20%, 30%, 40% or 50% open area. It is perfect for those who would like to unite quality and competitiveness.

Durability

Up to 2 years in mid European conditions. Clean removal within 6 months. Tack may increase over time. Not to be applied on: fresh paint or ink, polycarbonate, certain PVC (no exhaustive list). For critical substrates, please test prior to application.

Printing method

Solvent, eco-solvent, UV curable inks, screen printing and latex inks.

Shelf life

1 year, stored at +15 to +20° C (+59 to +68° F) and relative humidity between 45% and 65%.

Warranty

Continental Grafix products are warranted to be free of defects in material and manufacture at the time of shipment and to meet the specifications stated in the technical specification sheets. We will replace or refund the price of any Continental Grafix materials found to not meet our product specifications. In no case shall Continental Grafix be liable for any direct, indirect, or consequential damages, including labor or non-Continental Grafix materials charges. The determination of suitability of this product for any specific use is solely the responsibility of the user. No representations, guarantees or warranties of any kind are made to the accuracy of suitability for specific applications.



Advice

Prevent from contact with solvent or ammonia based cleaner. Clean window with soap and water. Rinse and dry glass after cleaning. ALWAYS clean and dry glass prior to application. Please respect our application instructions. made to the accuracy of suitability for specific applications

Uses

- Shop windows
- Building wraps
- Rear or side windows of busses and cars

Features & Benefit

- Removability up to 2 years under normal conditions (6 months without residue)
- Calendered vinyl features great dimensional stability
- Designed to be combined with the over laminate panoRama Cast or Protect (light curved and flat surfaces)



Technical information
panoRama Innova

Size	Width: 1.060 m Length: 50.00 m, 200 m, 400 m 1.372 m 25.00 m, 50.00 m, 200 m, 400 m 1.524 m 50.00 m, 200 m, 400 m	
Material	Self-adhesive, perforated vinyl film. Printable white front side and black reverse side for maximum contrast.	145µ +/- 10µ
Adhesive	Removable, semi-permanent clear adhesive	
Open area Printable area	20% / 30% / 40% / 50% open area 80% / 70% / 60% / 50% printable area	
Liner	Special liner finish	135g +/- 10µ
Certificate	Flammability	M1 and B1
	„Certified for HP Latex Inks“	300, 500, 1500 and 3000 Series
	TÜV Approval Germany	~ D5744 with panoRama Cast ~ D5745 without panoRama Cast
	Humidity resistance	good
	Solvent resistance	good
	Fire protection in railway vehicles	DIN EN 45545-2
Application	Minimum application temperature	+10°C / +50°F
	Minimum service range temperature	- 17°C / +0°F

CONTINENTAL GRAFIX AG

Lettenstrasse 2
6343 Rotkreuz
Switzerland

CONTACT

Phone: +41 41 763 66 88
Fax: +41 41 763 60 14
Email: info@continentalgrafix.com

MORE INFORMATION

For a detailed overview of our products please visit:
www.continentalgrafix.com